J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

TERMINAL PART NUMBER	SSHL-002T-P0.2
STRIP LENGTH (MM)	1.5

APPLICABLE WIRE SIZE	**CONDUCTOR BARREL**		**INSULATION BARREL**		**TENSILE (NEWTONS)**
	HEIGHT	WIDTH	HEIGHT	WIDTH	
30 AWG	0.44~0.48	0.7	*	0.85	5N
28 AWG	0.48~0.52	0.7	*	0.85	10N
26 AWG	0.52~0.56	0.7	*	0.85	20N

COMMENTS:

* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

GENERAL TOLERANCE:

CONDUCTOR HEIGHT	See above
CONDUCTOR WIDTH	- +/- 0.05
INSULATION HEIGHT	- N/A
INSULATION WIDTH	- +/- 0.05

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
PDS 10-11-06	PDS 10-11-06